

FEATURES

Standard range of motion adjuster offers 5 position for individual preferences
 100 Degree angle between seat pad and Back pad is optimal for quadricep contraction
 Without hamstring flexibility restrictions

MUSCLES USED

Quadriceps Femoris

MOTION DEVELOPED

Knee Extension



Prone Leg Curl

MAXNUM MA-B1001 S

FRAME AND CABLES

Oversized Frame Tubing	Yes
Frame Finish	Proprietary two-coat powder process
Cable Transmission	Internally Lubricated cables and fittings
Tube Thickness	3.0 mm.

WEIGHT STACK

Total Stack Weight	94 KG / 207 Lbs
Weight-Stack Pins	Magnetic Pins
Points of Adjustment	2 – point design
Guards and pulley Covers	Stack cover made of acrylic protects
Self-Lubricating weight stacks Bushings	Solid cold rolled steel plate, with Teflon inner bushings
Incremental Weight System	Yes

USER AMENITIES

Instructional Placards	Yes
Color-coded Pivots and Points of Adjustment	Yes
Personal Storage	No
Contoured Seating	Yes

TECH SPECS

Product Dimension (L x W x H)	152 x 99 x 135 / 60.8" x 39.6" x 54"
Product Weight	216 kg / 475 lbs
Certification	EN 957 Certified