

Maximize to Strong

FEATURES

Back pad and lower leg pad adjust without affecting knee alignment or start position
Standard range of motion adjuster for individual preference or anatomical limitations

MUSCLES USED

Hamstrings

MOTION DEVELOPED

Knee Flexion



Seated Dip

MAXNUM MA- B 1026 S

FRAME AND CABLES

Oversized Frame Tubing	Yes
Frame Finish	Proprietary two-coat powder process
Cable Transmission	Internally Lubricated cables and fittings
Tube Thickness	3.0 mm.

WEIGHT STACK

Total Stack Weight	109 KG / 240 Lbs
Weight-Stack Pins	Magnetic Pins
Points of Adjustment	No
Guards and pulley Covers	Stack cover made of acrylic protects
Self-Lubricating weight stacks Bushings	Solid cold rolled steel plate, with Teflon inner bushings
Incremental Weight System	Yes

USER AMENITIES

Instructional Placards	Yes
Color-coded Pivots and Points of Adjustment	Yes
Personal Storage	No
Contoured Seating	Yes

TECH SPECS

Product Dimension (L x W x H)	140 x 107 x 135 / 56" x 42.8" x 54"
Product Weight	230 kg / 506 lbs
Certification	ISO 9001 , EN 957 Certified